

SAFETY DATA SHEET

DOW DEUTSCHLAND ANLAGENGESELLSCHAFT MBH

Safety Data Sheet according to Reg. (EU) 2020/878

Product name: DOWSIL™ 799 EU Glaze and Go Sealant Grey

Revision Date: 29.03.2022 Version: 4.0

Date of last issue: 14.03.2022

Print Date: 30.03.2022

DOW DEUTSCHLAND ANLAGENGESELLSCHAFT MBH encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: DOWSIL™ 799 EU Glaze and Go Sealant Grey

UFI: XC30-A0C0-H001-GAU3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Adhesive, binding agents

1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION

DOW DEUTSCHLAND ANLAGENGESELLSCHAFT MBH RHEINGAUSTR. 34 65201 WIESBADEN GERMANY

Customer Information Number: (31) 115 67 2626

SDSQuestion@dow.com

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 00 49 4146 91 2333 **Local Emergency Contact:** 0049 4141 3679

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Skin sensitisation - Category 1 - H317

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

Hazard pictograms

Revision Date: 29.03.2022 Version: 4.0



Signal word: WARNING

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents and/or container to an approved waste disposal plant.

Supplemental information

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Contains 3-aminopropyltriethoxysilane; Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

2.3 Other hazards

This product contains octamethylcyclotetrasiloxane (D4) that has been identified by the Member State Committee of ECHA as fulfilling the PBT and vPvB criteria laid down in Annex XIII to Regulation (EC) No 1907/2006. See Section 12 for additional information.

Endocrine disrupting properties

Environment: The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

at levels of 0.1% or higher.

Human Health: The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Sealant

3.2 Mixtures

This product is a mixture.

Revision Date: 29.03.2022 Version: 4.0

CASRN 58190-57-1 EC-No. Not available Index-No.	_	>= 0,3 - < 4,7 %	Ethyl- tris(acetonoximo)- silane	STOT RE 2; H373 (Blood) Acute toxicity estimate Acute oral toxicity: > 2 500 mg/kg Acute dermal toxicity: > 2 000 mg/kg
CASRN 13463-67-7 EC-No. 236-675-5 Index-No.	01-2119489379-17	>= 0,8 - <= 1,8 %	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	Carc. 2; H351 Acute toxicity estimate Acute oral toxicity: > 10 000 mg/kg Acute inhalation toxicity: > 6,82 mg/l, 4 Hour, dust/mist Acute dermal toxicity: 10 000 mg/kg
CASRN 919-30-2 EC-No. 213-048-4 Index-No. 612-108-00-0	01-2119480479-24	>= 0,75 - <= 0,98 %		Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 1 479 mg/kg 2 665 mg/kg Acute inhalation toxicity: > 5 ppm, 6 Hour, vapour > 16 ppm, 6 Hour, vapour > 7,35 mg/l, 4 Hour, Aerosol Acute dermal toxicity: 4 041 mg/kg
CASRN 68928-76-7 EC-No. 273-028-6 Index-No.	01-2120770324-57	>= 0,15 - <= 0,22 %	Bis[(2-ethyl-2,5- dimethylhexanoyl)o xy](dimethyl)stanna ne	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute oral toxicity: 892 mg/kg Acute dermal toxicity: > 2 000 mg/kg
CASRN 556-67-2 EC-No. 209-136-7 Index-No. 014-018-00-1	_	>= 0,011 - <= 0,048	octamethylcyclotetr asiloxane [D4]	Flam. Liq. 3; H226 Repr. 2; H361f Aquatic Chronic 1; H410 M-Factor (Chronic aquatic toxicity): 10

Acute toxicity estimate
Acute oral toxicity:
> 4 800 mg/kg
Acute inhalation toxicity:
36 mg/l, 4 Hour, dust/mist
Acute dermal toxicity:
> 2 400 mg/kg

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: Rinse mouth with water. No emergency medical treatment necessary.

4.2 Most important symptoms and effects, both acute and delayed:

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical. Water spray.

Unsuitable extinguishing media: None known...

5.2 Special hazards arising from the substance or mixture

Page 4 of 28

Revision Date: 29.03.2022

Version: 4.0

Revision Date: 29.03.2022 Version: 4.0

Hazardous combustion products: Carbon oxides. Silicon oxides. Nitrogen oxides (NOx).

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health..

5.3 Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
- 6.2 Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- 6.3 Methods and materials for containment and cleaning up: Sweep up or vacuum up spillage and collect in suitable container for disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: Do not get on skin or clothing. Avoid contact with eyes. Do not swallow. Protect from moisture. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

7.2 Conditions for safe storage, including any incompatibilities: Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: Do not store in or use iron or steel containers.

Page 5 of 28

Revision Date: 29.03.2022 Version: 4.0

Storage class according to TRGS 510: Combustible Solids

7.3 Specific end use(s): See the technical data sheet on this product for further information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value				
3-aminopropyltriethoxysilane	Dow IHG	TWA	0,5 mg/m3				
Bis[(2-ethyl-2,5-	ACGIH	TWA	0,1 mg/m3 , Tin				
dimethylhexanoyl)oxy](dimet							
hyl)stannane							
	Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of cutaneous absorption						
	ACGIH	STEL	0,2 mg/m3 , Tin				
	Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of cutaneous absorption						
octamethylcyclotetrasiloxane	US WEEL	TWA	10 ppm				
[D4]							

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Recommended monitoring procedures

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with the Occupational Exposure Limits and the adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples should be analysed by an accredited laboratory.

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy); European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents); European Standard EN 482 (Workplace atmospheres -General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods. Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods. Health and Safety Executive (HSE). United Kingdom: Methods for the Determination of Hazardous Substances.

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany. L'Institut National de Recherche et de Securité, (INRS), France.

Derived No Effect Level

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10

Revision Date: 29.03.2022 Version: 4.0

μm]

Workers

Acute systemic effects		Acute local effects		_	n systemic ects	Long-term local effects		
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	10 mg/m3	

Consumers

Acute systemic effects		Acute local effects		Long-term systemic effects			Long-term local effects		
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	700 mg/kg bw/day	n.a.	n.a.

3-aminopropyltriethoxysilane

Workers

Acute systemic effects		Acute local effects		Long-term systemic effects		Long-term local effects		
	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
	8,3 mg/kg	59 mg/m3	n.a.	n.a.	8,3 mg/kg	59 mg/m3	n.a.	n.a.
	bw/day				bw/day			

Consumers

Concami	,, ,								
Acute systemic effects		Acute local effects		Long-term systemic effects			Long-term local effects		
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
5 mg/kg	17,4	5 mg/kg	n.a.	n.a.	5 mg/kg	17	5 mg/kg	n.a.	n.a.
bw/day	mg/m3	bw/day			bw/day	mg/m3	bw/day		

octamethylcyclotetrasiloxane [D4]

Workers

11011010							
Acute systemic effects		Acute local effects		Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	73 mg/m3	n.a.	73 mg/m3

Consumers

Acute systemic effects		Acute local effects		Long-term systemic effects			Long-term local effects		
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	13	3,7	n.a.	13
						mg/m3	mg/kg bw/day		mg/m3

Predicted No Effect Concentration

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

,	•
Compartment	PNEC
Fresh water	0,184 mg/l
Marine water	0,0184 mg/l

Page 7 of 28

Revision Date: 29.03.2022 Version: 4.0

Intermittent use/release	0,193 mg/l
Sewage treatment plant	100 mg/l
Fresh water sediment	1000 mg/kg
Marine sediment	100 mg/kg
Soil	100 mg/kg

3-aminopropyltriethoxysilane

Compartment	PNEC
Fresh water	0,33 mg/l
Marine water	0,033 mg/l
Fresh water sediment	0,26 mg/kg
Marine sediment	0,026 mg/kg
Soil	0,04 mg/kg
Sewage treatment plant	13 mg/l

octamethylcyclotetrasiloxane [D4]

Compartment	PNEC
Fresh water	0,0015 mg/l
Marine water	0,00015 mg/l
Fresh water sediment	3 mg/kg
Marine sediment	0,3 mg/kg
Soil	0,54 mg/kg
Sewage treatment plant	10 mg/l
Oral	41 mg/kg food

8.2 Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

Skin protection

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may

Revision Date: 29.03.2022 Version: 4.0

> offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or quidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

Use the following CE approved air-purifying respirator: Organic vapor cartridge, type A (boiling point >65 °C, meeting standard EN 14387).

Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state solid Color arev

characteristic Odor **Odor Threshold** No data available

Not applicable, substance/mixture is non-soluble (in water)

Melting point/freezing point

Melting point/range No data available Freezing point not determined Boiling point or initial boiling point and boiling range Boiling point (760 mmHg) Not applicable

Flash point closed cup >100 °C

Flammability (solid, gas) Not classified as a flammability hazard

Flammability (liquids) Not applicable, solid Lower explosion limit No data available **Upper explosion limit** No data available **Vapor Pressure** Not applicable Relative Vapor Density (air = 1) No data available

Relative Density (water = 1) 1.03

Solubility(ies)

Page 9 of 28

Revision Date: 29.03.2022 Version: 4.0

Water solubility insoluble

Partition coefficient: n- not determined

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableKinematic ViscosityNot applicable, solid

Particle characteristics

Particle size not determined

9.2 Other information

Molecular weightNo data availableDynamic ViscosityNot applicableExplosive propertiesNot explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Self-heating substances The substance or mixture is not classified as self heating.

Evaporation Rate (Butyl Acetate Not applicable

= 1)

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: Not classified as a reactivity hazard.

10.2 Chemical stability: Stable under normal conditions.

10.3 Possibility of hazardous reactions: Can react with strong oxidizing agents.

10.4 Conditions to avoid: Do not expose to temperatures above 212 °F/100 °C. Exposure to moisture

10.5 Incompatible materials: Avoid contact with oxidizing materials.

10.6 Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Revision Date: 29.03.2022 Version: 4.0

Acute Toxicity Endpoints:

Acute oral toxicity

Information for the Product:

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 5 000 mg/kg Estimated.

Information for components:

Ethyl-tris(acetonoximo)-silane

LD50, Rat, female, > 2 500 mg/kg No deaths occurred at this concentration.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

LD50, Rat, > 10 000 mg/kg

3-aminopropyltriethoxysilane

LD50, Rat, female, 1 479 mg/kg

LD50, Rat, male, 2 665 mg/kg

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

LD50, Rat, male and female, 892 mg/kg OECD 401 or equivalent

octamethylcyclotetrasiloxane [D4]

LD50, Rat, male, > 4 800 mg/kg No deaths occurred at this concentration.

Acute dermal toxicity

Information for the Product:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s): LD50, Rabbit, > 2 000 mg/kg Estimated.

Information for components:

Ethyl-tris(acetonoximo)-silane

The dermal LD50 has not been determined.

Page 11 of 28

Revision Date: 29.03.2022 Version: 4.0

> For similar material(s): LD50. Rat. male and female. > 2 000 mg/kg No deaths occurred at this concentration.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

LD50, Rabbit, 10 000 mg/kg

3-aminopropyltriethoxysilane

Based on product testing: LD50, Rabbit, male and female, 4 041 mg/kg

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

LD50, Rat. > 2000 mg/kg

octamethylcyclotetrasiloxane [D4]

LD50, Rat, male and female, > 2 400 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

Information for the Product:

At room temperature, exposure to vapor is minimal due to low volatility. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

Information for components:

Ethyl-tris(acetonoximo)-silane

The LC50 has not been determined.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

LC50, Rat, male, 4 Hour, dust/mist, > 6,82 mg/l No deaths occurred at this concentration.

3-aminopropyltriethoxysilane

Based on product testing: LC50, Rat, male, 6 Hour, vapour, > 5 ppm No deaths occurred at this concentration.

Based on product testing: LC50, Rat, female, 6 Hour, vapour, > 16 ppm No deaths occurred at this concentration.

Based on product testing: LC50, Rat, male and female, 4 Hour, Aerosol, > 7,35 mg/l

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

As product: The LC50 has not been determined.

octamethylcyclotetrasiloxane [D4]

LC50, Rat, male and female, 4 Hour, dust/mist, 36 mg/l OECD Test Guideline 403

Skin corrosion/irritation

Revision Date: 29.03.2022 Version: 4.0

Information for the Product:

Based on information for component(s):

Prolonged exposure not likely to cause significant skin irritation.

Information for components:

Ethyl-tris(acetonoximo)-silane

Brief contact is essentially nonirritating to skin.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Essentially nonirritating to skin.

3-aminopropyltriethoxysilane

Brief contact may cause severe skin burns. Symptoms may include pain, severe local redness and tissue damage.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Brief contact may cause skin irritation with local redness.

octamethylcyclotetrasiloxane [D4]

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

Information for the Product:

Based on information for component(s): May cause slight temporary eye irritation.

Corneal injury is unlikely.

May cause mild eye discomfort.

Information for components:

Ethyl-tris(acetonoximo)-silane

Essentially nonirritating to eyes.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Solid or dust may cause irritation due to mechanical action.

3-aminopropyltriethoxysilane

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Vapor or mist may cause eye irritation.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

May cause slight eye irritation.

May cause slight temporary corneal injury.

octamethylcyclotetrasiloxane [D4]

Revision Date: 29.03.2022 Version: 4.0

Essentially nonirritating to eyes.

Sensitization

For skin sensitization:

May cause an allergic skin reaction.

Information for the Product:

For skin sensitization:

Contains component(s) which have caused allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant information found.

Information for components:

Ethyl-tris(acetonoximo)-silane

For similar material(s):

Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Did not demonstrate the potential for contact allergy in mice.

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

3-aminopropyltriethoxysilane

For skin sensitization:

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

octamethylcyclotetrasiloxane [D4]

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Revision Date: 29.03.2022 Version: 4.0

Specific Target Organ Systemic Toxicity (Single Exposure)

Information for the Product:

Product test data not available.

Information for components:

Ethyl-tris(acetonoximo)-silane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

3-aminopropyltriethoxysilane

Material is corrosive. Material is not classified as a respiratory irritant; however, upper respiratory tract irritation or corrosivity may be expected.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Available data are inadequate to determine single exposure specific target organ toxicity.

octamethylcyclotetrasiloxane [D4]

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Information for the Product:

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Ethyl-tris(acetonoximo)-silane

Based on physical properties, not likely to be an aspiration hazard.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Based on physical properties, not likely to be an aspiration hazard.

3-aminopropyltriethoxysilane

Based on available information, aspiration hazard could not be determined.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Based on physical properties, not likely to be an aspiration hazard.

octamethylcyclotetrasiloxane [D4]

May be harmful if swallowed and enters airways.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Page 15 of 28

Revision Date: 29.03.2022 Version: 4.0

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Information for the Product:

Product test data not available.

Information for components:

Ethyl-tris(acetonoximo)-silane

In animals, effects have been reported on the following organs: Blood

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Repeated excessive inhalation exposures to dusts may cause respiratory effects. In animals, effects have been reported on the following organs:

Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

3-aminopropyltriethoxysilane

In animals, effects have been reported on the following organs: Liver.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

In animals, effects have been reported on the following organs:

Blood

Kidney

Liver

Immune system.

octamethylcyclotetrasiloxane [D4]

In animals, effects have been reported on the following organs:

Kidney.

Liver.

Respiratory tract.

Female reproductive organs.

Carcinogenicity

Information for the Product:

Product test data not available.

Information for components:

Ethyl-tris(acetonoximo)-silane

No relevant data found.

Revision Date: 29.03.2022 Version: 4.0

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Lung fibrosis and tumors have been observed in rats exposed to titanium dioxide in two lifetime inhalation studies. Effects are believed to be due to overloading of the normal respiratory clearance mechanisms caused by the extreme study conditions. Workers exposed to titanium dioxide in the workplace have not shown an unusual incidence of chronic respiratory disease or lung cancer. Titaniumdioxide was not carcinogenic in laboratory animals in lifetime feeding studies. Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

3-aminopropyltriethoxysilane

Did not cause cancer in laboratory animals.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

octamethylcyclotetrasiloxane [D4]

Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

Teratogenicity

Information for the Product:

Product test data not available.

Information for components:

Ethyl-tris(acetonoximo)-silane

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

No relevant data found.

3-aminopropyltriethoxysilane

Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

octamethylcyclotetrasiloxane [D4]

Did not cause birth defects or any other fetal effects in laboratory animals.

Revision Date: 29.03.2022 Version: 4.0

Reproductive toxicity

Information for the Product:

Product test data not available.

Information for components:

Ethyl-tris(acetonoximo)-silane

For similar material(s): In animal studies, did not interfere with reproduction.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

No relevant data found.

3-aminopropyltriethoxysilane

In animal studies, did not interfere with fertility.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

octamethylcyclotetrasiloxane [D4]

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. In animal studies, has been shown to interfere with fertility.

Mutagenicity

Information for the Product:

Product test data not available.

Information for components:

Ethyl-tris(acetonoximo)-silane

For similar material(s): In vitro genetic toxicity studies were negative.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

3-aminopropyltriethoxysilane

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Bis[(2-ethyl-2.5-dimethylhexanoyl)oxy](dimethyl)stannane

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

octamethylcyclotetrasiloxane [D4]

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Product name: DOWSIL™ 799 EU Glaze and Go Sealant Grey
Revision Date: 29.03.2022
Version: 4.0

11.2 Information on other hazards

Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Information for components:

Ethyl-tris(acetonoximo)-silane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

3-aminopropyltriethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

octamethylcyclotetrasiloxane [D4]

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Additional information

During curing, the product releases small amounts of acetonoxime. Liver tumors have been observed in male rats exposed to acetonoxime via drinking water. The relevance of these findings to humans is not known at this stage.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

12.1 Toxicity

Ethyl-tris(acetonoximo)-silane
Acute toxicity to fish

Revision Date: 29.03.2022 Version: 4.0

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Based on data from similar materials

LC50, Pimephales promelas (fathead minnow), 96 Hour, 696,76 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

Based on data from similar materials

EC50, Daphnia magna (Water flea), 48 Hour, 678,73 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

Based on data from similar materials

EC50, Selenastrum capricornutum (green algae), 72 Hour, 315,36 mg/l, OECD Test Guideline 201

Based on data from similar materials

NOEC, Selenastrum capricornutum (green algae), 72 Hour, 62,34 mg/l, OECD Test Guideline 201

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

NOEC, Leuciscus idus (Golden orfe), static test, 48 Hour, > 1 000 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 1 000 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, 3 Hour, > 1 000 mg/l, OECD Test Guideline 209

3-aminopropyltriethoxysilane

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Danio rerio (zebra fish), semi-static test, 96 Hour, > 934 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 331 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, > 1000 mg/l

NOEC, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 1,3 mg/l

Toxicity to bacteria

Product name: DOWSIL™ 799 EU Glaze and Go Sealant Grey **Revision Date: 29.03.2022** Version: 4.0

EC50. Pseudomonas putida, 5.75 Hour, Respiration rates., 43 mg/l

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Acute toxicity to fish

Material is harmful to aquatic organisms (LC50/EC50/IC50 between 10 and 100 mg/L in the most sensitive species).

For similar material(s):

LC50, Zebra fish (Danio/Brachydanio rerio), semi-static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna, static test, 48 Hour, 39 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Algae (Scenedesmus subspicatus), Growth rate, 72 Hour, Growth rate, 7.6 mg/l, OECD Test Guideline 201 or Equivalent

For similar material(s):

NOEC, Algae (Scenedesmus subspicatus), Growth rate, 72 Hour, Growth rate, 1,1 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

For similar material(s):

EC50, Bacteria, 3 Hour, Respiration rates., 14 mg/l

octamethylcyclotetrasiloxane [D4]

Acute toxicity to fish

Based on testing of comparable products: The estimated maximum agueous concentration of Octamethyl Cyclotetrasiloxane (D4) from migration to water from the product as supplied is below the D4 established no-effect threshold (< 0.0079 mg/L) for aquatic organisms.

Chronic toxicity to aquatic invertebrates

Based on testing for product(s) in this family of materials:

Not classified due to data which are conclusive although insufficient for classification.

12.2 Persistence and degradability

Ethyl-tris(acetonoximo)-silane

Biodegradability: Material is expected to be readily biodegradable.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Biodegradability: Biodegradation is not applicable.

3-aminopropyltriethoxysilane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail **Biodegradation:** 67 % Exposure time: 28 d

Method: OECD Test Guideline 301A or Equivalent

Stability in Water (1/2-life)

Page 21 of 28

Revision Date: 29.03.2022 Version: 4.0

Hydrolysis, half-life, 8.5 Hour, pH 7, Half-life Temperature 24.7 °C

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Biodegradability: For similar material(s): Material is expected to biodegrade very slowly (in

the environment). Fails to pass OECD/EEC tests for ready biodegradability.

For similar material(s): 10-day Window: Fail

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

octamethylcyclotetrasiloxane [D4]

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable **Biodegradation:** 3.7 % Exposure time: 28 d

Method: OECD Test Guideline 310

Stability in Water (1/2-life)

Hydrolysis, DT50, 3,9 d, pH 7, Half-life Temperature 25 °C, OECD Test Guideline 111

12.3 Bioaccumulative potential

Ethyl-tris(acetonoximo)-silane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0,2

3-aminopropyltriethoxysilane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1,7 at 20 °C Calculated.

Bioconcentration factor (BCF): 3,4 Cyprinus carpio (Carp) 56 d

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Bioaccumulation: No relevant data found.

octamethylcyclotetrasiloxane [D4]

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and

Partition coefficient: n-octanol/water(log Pow): 6,49 Measured

Bioconcentration factor (BCF): 12 400 Pimephales promelas (fathead minnow) Measured

12.4 Mobility in soil

Ethyl-tris(acetonoximo)-silane

No relevant data found.

3-aminopropyltriethoxysilane

No relevant data found.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

octamethylcyclotetrasiloxane [D4]

Page 22 of 28

Revision Date: 29.03.2022 Version: 4.0

Partition coefficient (Koc): 16596 OECD Test Guideline 106

12.5 Results of PBT and vPvB assessment

Ethyl-tris(acetonoximo)-silane

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

3-aminopropyltriethoxysilane

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Bis[(2-ethyl-2.5-dimethylhexanoyl)oxy](dimethyl)stannane

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

octamethylcyclotetrasiloxane [D4]

Octamethylcyclotetrasiloxane (D4) meets the current criteria for PBT and vPvB under REACh Annex XIII or other regionally specific criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

This substance is considered to be persistent, bioaccumulating and toxic (PBT).

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Ethyl-tris(acetonoximo)-silane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

3-aminopropyltriethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Page 23 of 28

Revision Date: 29.03.2022 Version: 4.0

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

octamethylcyclotetrasiloxane [D4]

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

12.7 Other adverse effects

Ethyl-tris(acetonoximo)-silane

This substance is not on the Montreal Protocol list of substances that deplete the ozone laver.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

3-aminopropyltriethoxysilane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

octamethylcyclotetrasiloxane [D4]

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID):

14.1 UN number or ID number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable 14.4 Packing group Not applicable

Page 24 of 28

Revision Date: 29.03.2022 Version: 4.0

14.5 Environmental hazards Not considered environmentally hazardous based on

available data.

14.6 Special precautions for user No data available.

Classification for INLAND waterways (ADNR/ADN):

Consult your Dow contact before transporting by inland waterway

Classification for SEA transport (IMO-IMDG):

14.1 UN number or ID number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable 14.4 Packing group Not applicable

14.5 Environmental hazards Not considered as marine pollutant based on available data.

14.6 Special precautions for user No data available.

14.7 Maritime transport in bulk

according to IMO instruments

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

14.1 UN number or ID number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable 14.4 Packing group Not applicable 14.5 Environmental hazards Not applicable 14.6 Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACh Regulation (EC) No 1907/2006

This product contains only components that have been either registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No.

Page 25 of 28

Revision Date: 29.03.2022 Version: 4.0

1907/2006 (REACH).. The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Bis[(2-ethyl-2,5dimethylhexanoyl)oxy](dimethyl)stannane (Number on list 20) octamethylcyclotetrasiloxane [D4] (Number on list 70)

Authorisation status under REACH:

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

CAS-No.: 556-67-2 Name: octamethylcyclotetrasiloxane [D4]

Authorisation status: listed in the Candidate List of Substances of Very High Concern for Authorisation

Authorisation number: Not available

Sunset date: Not available

Exempted (Categories of) Uses: Not available

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: Not applicable

Wassergefährdungsklasse (Deutschland)

WGK 2: obviously hazardous to water

Further information

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture.

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H351	Suspected of causing cancer if inhaled.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated

Page 26 of 28

Revision Date: 29.03.2022 Version: 4.0

swallowed.

H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Skin Sens. - 1 - H317 - Calculation method

Revision

Identification Number: 4104140 / A287 / Issue Date: 29.03.2022 / Version: 4.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this

Legend

Logona	
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
Dow IHG	Dow Industrial Hygiene Guideline
STEL	Short-term exposure limit
TWA	Time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)
Acute Tox.	Acute toxicity
Aquatic Chronic	Long-term (chronic) aquatic hazard
Carc.	Carcinogenicity
Eye Dam.	Serious eye damage
Flam. Liq.	Flammable liquids
Repr.	Reproductive toxicity
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - AmericanSociety for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS -Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL -No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development;

Page 27 of 28

Revision Date: 29.03.2022 Version: 4.0

OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR -(Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA-Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW DEUTSCHLAND ANLAGENGESELLSCHAFT MBH urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

DE